


Product Specifications	Standard	Rolls & Tiles	Raised Access Floor Tiles (Square and Plank)
 Composition	-	87%vinyl + 13% polyester + backing100% vinyl	87%vinyl + % polyester + backing100% vinyl
 Weight (g/m²) (oz/sq ft)	ISO 8543:1998	3500 g/m² (11.5 oz/sq ft) +13% / -10%	4275 g/m² (14.0 oz/sq ft) +13% / -10%
 Thickness (mm.) (in)	ISO 1765:1986	2.60 mm (0.10 in)	3.30 mm (0.13 in)
 Light Fastness (Grey scale: 1-5)	EN ISO 4892:2006 (exterior)	>4/5	>4/5
 Light Fastness (Blue scale: 1-8)	EN ISO 105B02:2001 (interior)	>7/8	>7/8
 Dimensional Stability %	EN ISO 23999:2012	≤0.25%	≤0.25%
 Residual Indentation	EN ISO 24343-1:2012	<0.10 mm (<0.003 in)	<0.10 mm (<0.003 in)
 Castor Chair Test	EN 985:2002	Intensive use	Intensive use
 Sound Insulation	EN ISO 10140-3:2011	14 dB	15 dB
 Thermal Resistance	EN 12667:2001	< 0.15m² K/W	< 0.15m² K/W
 Static Electricity	EN 1815:1997	< 2 kV	< 2 kV
 Slip Resistance	EN 13893:2003	>0.4	>0.4
Slip Resistance	DIN 51130:2014	R9	R9
Slip Resistance	ASTM C1028-96 Static Coefficient	Wet: 0.62; Dry: 0.70	Wet: 0.62; Dry: 0.70
 Fire Classification	EN 13501-1:2007	Bfl-S1	Bfl-S1
 Fire Classification	ASTM E648 (NFPA 253)	Class 1	Class 1
Antibacterial activity	ASTM E 2180-07(2012) ASTM G21:2013	Inhibition of bacterial growth & Antifungal activity	Inhibition of bacterial growth & Antifungal activity
 Roll Width	-	200 cm 78.740 in	
 Roll Length	-	10 lm (32.81 ft) 20 lm (65.62 ft)	
CE Certificate	EN 14041:2004	0338-CPR-2002	0338-CPR-2002
Use Classification	EN 1307:2014	Heavy Commercial 	
 Tile Dimensions			

All specifications are based on average values and may deviate. The values are for guidance and not contractual. Subject to technical modifications.
The straight weft is not an inherent condition. Weaving technology features colour effects because of light, making it an exclusive and unique product. Also bicolour yarns create a randomly harmonious effect. These effects are no ground for claims.

vertisol
contemporary weavers

C. 17Km. 18, 920-08403 Granollers (Barcelona), Spain
T. (+34) 93 840 14 44 · F. (+34) 93 849 72 19

fitnice® is a registered trademark of Vertisol Internacional SRL.

fitnice.com
info@fitnice.com

  fitniceflooring



ISO 9001:2015 and
ISO 14001:2015
certified company



CE
Vertisol Internacional, SRL
0338-CPR-2002



Product Specifications	Standard	Rolls & Tiles (Rolls only for corridors)	Raised Access Floor Tiles (Square and Plank)
Composition	-	75%vinyl + 25% polyester + backing100% vinyl	75%vinyl + 25% polyester + backing100% vinyl
Weight (g/m²) (oz/sq ft)	ISO 8543:1998	3100 g/m² (10.2 oz/sq ft) +13% / -10%	4300 g/m² (14.1oz/sq ft) +13% / -10%
Thickness (mm.) (in)	ISO 1765:1986	2.30 mm (0.09 in)	3.00 mm (0.12 in)
Light Fastness (Grey scale: 1-5)	EN ISO 4892:2006 (exterior)	>4/5	>4/5
Light Fastness (Blue scale: 1-8)	EN ISO 105B02:2001 (interior)	>7/8	>7/8
Dimensional Stability %	EN ISO 23999:2012	≤0.25%	≤0.25%
Residual Indentation	EN ISO 24343-1:2012	<0.10 mm (<0.003 in)	<0.10 mm (<0.003 in)
Castor Chair Test	EN 985:2002	Intensive use	Intensive use
Sound Insulation	EN ISO 10140-3:2011	12 dB	13 dB
Thermal Resistance	EN 12667:2001	< 0.15m² K/W	< 0.15m² K/W
Static Electricity	EN 1815:1997	< 2 kV	< 2 kV
Slip Resistance	EN 13893:2003	>0.4	>0.4
Slip Resistance	DIN 51130:2014	R10	R10
Slip Resistance	ASTM C1028-96 Static Coefficient	Wet: 0.79; Dry: 0.86	Wet: 0.79; Dry: 0.86
Fire Classification	EN 13501-1:2007	Bfl-S1	Bfl-S1
Fire Classification	ASTM E648 (NFPA 253)	Class 1	Class 1
Antibacterial activity	ASTM E 2180-07(2012) ASTM G21:2013	Inhibition of bacterial growth & Antifungal activity	Inhibition of bacterial growth & Antifungal activity
Roll Width	-	200 cm 78.740 in	
Roll Length	-	10 lm (32.81 ft) 20 lm (65.62 ft)	
CE Certificate	EN 14041:2004	0338-CPR-2002	0338-CPR-2002
Use Classification	EN 1307:2014	Heavy Commercial	
Tile Dimensions	Square Plank Brick Diamond Hexagon E. Triangle I. Triangle Trap Arcade		

All specifications are based on average values and may deviate. The values are for guidance and not contractual. Subject to technical modifications. The straight weft is not an inherent condition. Weaving technology features colour effects because of light, making it an exclusive and unique product. Also bicolour yarns create a randomly harmonious effect. These effects are no ground for claims.

vertisol
contemporary weavers

C. 17Km.18, 920·08403 Granollers (Barcelona), Spain
T. (+34) 93 840 14 44 · F. (+34) 93 849 72 19

fitnice® is a registered trademark of Vertisol Internacional SRL.

fitnice.com
info@fitnice.com

fitniceflooring

Product Specifications	Standard	Rolls & Tiles	Raised Access Floor Tiles (Square and Plank)
 Composition	-	91%vinyl + 9% polyester + backing100% vinyl	91%vinyl + 9% polyester + backing100% vinyl
 Weight (g/m²) (oz/sq ft)	ISO 8543:1998	3500 g/m² (11.5 oz/sq ft) +13% / -10%	4275 g/m² (14.0 oz/sq ft) +13% / -10%
 Thickness (mm) (in)	ISO 1765:1986	2.70 mm (0.11 in)	3.35 mm (0.13 in)
 Light Fastness (Grey scale: 1-5)	EN ISO 4892:2006 (exterior)	>4/5	>4/5
 Light Fastness (Blue scale: 1-8)	EN ISO 105B02:2001 (interior)	>7/8	>7/8
 Dimensional Stability %	EN ISO 23999:2012	≤0.25%	≤0.25%
 Residual Indentation	EN ISO 24343-1:2012	<0.30 mm (<0.011 in)	<0.30 mm (<0.011 in)
 Castor Chair Test	EN 985:2002	Intensive use	Intensive use
 Sound Insulation	EN ISO 10140-3:2011	14 dB	15 dB
 Thermal Resistance	EN 12667:2001	< 0.15m² K/W	< 0.15m² K/W
 Static Electricity	EN 1815:1997	< 2 kV	< 2 kV
 Slip Resistance	EN 13893:2003	>0.4	>0.4
Slip Resistance	DIN 51130:2014	R9	R9
Slip Resistance	ASTM C1028-96 Static Coefficient	Wet: 0.59; Dry: 0.72	Wet: 0.59; Dry: 0.72
 Fire Classification	EN 13501-1:2007	Bfl-S1	Bfl-S1
 Fire Classification	ASTM E648 (NFPA 253)	Class 1	Class 1
Antibacterial activity	ASTM E 2180-07(2012) ASTM G21:2013	Inhibition of bacterial growth & Antifungal activity	Inhibition of bacterial growth & Antifungal activity
 Roll Width	-	200 cm 78.740 in	
 Roll Length	-	10 lm (32.81 ft) 20 lm (65.62 ft)	
CE Certificate	EN 14041:2004	0338-CPR-2002	0338-CPR-2002
Use Classification	EN 1307:2014	Heavy Commercial 	
 Tile Dimensions	Square Plank Brick Diamond Hexagon E. Triangle I. Triangle Trap Arcade 		

All specifications are based on average values and may deviate. The values are for guidance and not contractual. Subject to technical modifications.
The straight weft is not an inherent condition. Weaving technology features colour effects because of light, making it an exclusive and unique product. Also bicolour yarns create a randomly harmonious effect. These effects are no ground for claims.

vertisol
contemporary weavers

C. 17Km. 18, 920-08403 Granollers (Barcelona), Spain
T. (+34) 93 840 14 44 · F. (+34) 93 849 72 19


fitnice.com
info@fitnice.com

fitnice® is a registered trademark of Vertisol Internacional SRL.

  fitniceflooring

Product Specifications	Standard	Rolls & Tiles	Raised Access Floor Tiles (Square and Plank)
 Composition	-	75% vinyl + 25% polyester + backing 100% vinyl	75% vinyl + 25% polyester + backing 100% vinyl
 Weight (g/m²) (oz/sq ft)	ISO 8543:1998	2900 g/m² (9.5 oz/sq ft) +13% / -10%	4500 g/m² (14.75 oz/sq ft) +13% / -10%
 Thickness (mm.) (in)	ISO 1765:1986	2.25 mm (0.09 in)	2.90 mm (0.11 in)
 Light Fastness (Grey scale: 1-5)	EN ISO 4892:2006 (exterior)	>4/5	>4/5
 Light Fastness (Blue scale: 1-8)	EN ISO 105B02:2001 (interior)	>7/8	>7/8
 Dimensional Stability %	EN ISO 23999:2012	≤0.25%	≤0.25%
 Residual Indentation	EN ISO 24343-1:2012	<0.10 mm (<0.003 in)	<0.10 mm (<0.003 in)
 Castor Chair Test	EN 985:2002	Intensive use	Intensive use
 Sound Insulation	EN ISO 10140-3:2011	13 dB	14 dB
 Thermal Resistance	EN 12667:2001	< 0.15m² K/W	< 0.15m² K/W
 Static Electricity	EN 1815:1997	< 2 kV	< 2 kV
 Slip Resistance	EN 13893:2003	>0.4	>0.4
Slip Resistance	DIN 51130:2014	R10	R10
Slip Resistance	ASTM C1028-96 Static Coefficient	Wet: 0.65; Dry: 0.75	Wet: 0.65; Dry: 0.75
 Fire Classification	EN 13501-1:2007	Bfl-S1	Bfl-S1
 Fire Classification	ASTM E648 (NFPA 253)	Class 1	Class 1
Antibacterial activity	ASTM E 2180-07(2012) ASTM G21:2013	Inhibition of bacterial growth & Antifungal activity	Inhibition of bacterial growth & Antifungal activity
 Roll Width	-	200 cm (78.740 in)	
 Roll Length	-	10 lm (32.81 ft) 20 lm (65.62 ft)	
CE Certificate	EN 14041:2004	0338-CPR-2002	0338-CPR-2002
Use Classification	EN 1307:2014	Heavy Commercial 	

Tile Dimensions



All specifications are based on average values and may deviate. The values are for guidance and not contractual. Subject to technical modifications. The straight weft is not an inherent condition. Weaving technology features colour effects because of light, making it an exclusive and unique product. Also bicolour yarns create a randomly harmonious effect. These effects are no ground for claims.

vertisol
contemporary weavers

C.17Km.18,920-08403 Granollers (Barcelona), Spain
T. (+34) 93 840 14 44 · F. (+34) 93 849 72 19

fitnice® is a registered trademark of Vertisol Internacional SRL.

fitnice.com
info@fitnice.com

  fitniceflooring



ISO 9001:2015 and
ISO 14001:2015
certified company

